

Ultra Body Filler

Description:

Bodyline Ultra Body Filler is a two component paste used for the filling of holes and imperfections in most substrates such as steel, galvanised steel, aluminium and GRP. It has been specially formulated for the professional using the latest technology in lightweight easy to sand body fillers. It combines excellent filling properties together with the easiest sanding of all the Bodyline fillers.

Surface Preparation & Instructions For Use:

Bodyline Ultra Body Filler can be used on the following surfaces:-

- Bare metal - degrease and abrade with P80 paper.
- Original paint surfaces (with the exception of thermoplastic acrylics) - degrease and abrade with P180 paper.
- GRP - degrease and abrade with P80 paper.

Mixing Ratio:

100 parts by weight Bodyline Ultra Body Filler to 2 parts by weight Bodyline hardener for polyester filler. The exact mixing ratio is not critical, although over or under catalysation may affect the gel time. Excess hardener will not significantly speed up the gel time and could lead to bleed through and bleaching when over-painting.

Pot Life:

Once mixed, 4-5 mins. at 20°C with 2% hardener.

Tools:

Mixing board, filler knife, plastic or metal spatula.

Drying Time:

Sandable after 15 mins. at 20°C. **Important** - This filler is very easy to sand and therefore recommend that nothing coarser or lower than P80 paper is used.

Over-Painting:

Bodyline Ultra Body Filler can be over-painted directly with most paint systems.

Available Sizes:

1L Bag	- Part No: BUBFB
1.3L Dispenser	- Part No: BUBF13
3L Tin	- Part No: BUBF3

VOC Information:

Product Category IIB.b, EU limit governing this product is 250g/litre. The VOC content of this product is 100g/litre.

Safety:

See separate Material Safety Data Sheet (MSDS)

FOR PROFESSIONAL USE ONLY

Brown Brothers Distribution Ltd.,
Wellington House, Starley Way,
Birmingham International Park, Solihull, B37 7HB.
Tel: 0121 781 7208 Fax: 0121 781 7307
www.brownbrothers.com