

PO Box 162, Needham Road, Stowmarket IP14 2ZR

Tel: 01449 778 333 Fax: 01449 773 472

## **Safety Data Sheet: Glazing Primer**

**Product Name** : Glazing Primer

**Product Code** : BDBBP30 **Revision Date** : 19/08/2015

**Revision Number** : 2

Company : Brown Brothers Distribution Limited

Address : PO Box 162

> **Needham Road** Stowmarket **IP14 2ZR**

Telephone : 0044 (0) 1449 778333 : 0044 (0) 1449 773472 Fax

: enquiries@brownbrothers.com **Email** 

Relevant identified uses of the substance or mixture and uses advised against Use of substance / mixture: PC9a: Coatings and paints, thinners, paint removers.

**Section 2: Hazards identification** 

2.1. Classification of the substance or mixture

Classification under CHIP: Sens.: R42/43; Xi: R36; F: R11; -: R67

Classification under CLP: Flam. Liq. 2: H225; Resp. Sens. 1: H334; Eye Irrit. 2: H319; Skin

Sens. 1: H317: STOT SE 3: H336: -: EUH208

Most important adverse effects: May cause sensitisation by inhalation and skin contact.

Irritating to eyes. Highly

flammable. Vapours may cause drowsiness and dizziness.

2.2. Label elements

**Label elements under CLP:** 

Hazard statements: H225: Highly flammable liquid and vapour.

H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H319: Causes serious eye irritation.

H317: May cause an allergic skin reaction.

H336: May cause drowsiness or dizziness.

EUH208: Contains diphenylmethane diisocyanate (isomers and homologues). May

produce an allergic reaction.

Signal words: Danger

Hazard pictograms: GHS02: Flame

**GHS07: Exclamation mark** GHS08: Health hazard

## bodyline

**Brown Brothers Distribution Ltd** 

PO Box 162, Needham Road, Stowmarket IP14 2ZR

Tel: 01449 778 333 Fax: 01449 773 472







**Precautionary statements:** P501: Dispose of contents/container to an approved waste disposal according to

local/regional/national/international regulations.

P210: Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P241: Use explosion-proof electrical/ventilating/lighting equipment.

P303+361+353: IF ON SKIN (or hair): Remove immediately all contaminated clothing.

Rinse skin with water/shower.

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P405: Store locked up.

**Label elements under CHIP:** 

Hazard symbols: Highly flammable.

Irritant.





Risk phrases: R42/43: May cause sensitisation by inhalation and skin contact.

R36: Irritating to eyes. R11: Highly flammable.

R67: Vapours may cause drowsiness and dizziness.

Safety phrases: S23: Do not breathe in.

S24: Avoid contact with skin.

S37: Wear suitable gloves.

S45: In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

S63: In case of accident by inhalation, remove casualty to fresh air and keep at rest.

Precautionary phrases: Contains diphenylmethane diisocyanate (isomers and homologues).

May produce an allergic reaction.

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

### **Section 3: Composition/information on ingredients**



PO Box 162, Needham Road, Stowmarket IP14 2ZR

Tel: 01449 778 333 Fax: 01449 773 472

#### 3.2. Mixtures

## **Hazardous ingredients:**

ETHYL METHYL KETONE

	I E I CITE			
EINECS	CAS	CHIP Classification	CLP Classification	Percent
201-159-0	78-93-3	F: R11; Xi: R36; -: R66; -: R67	Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336; -: EUH066	75.000%
2-METHOXY-1	-METHYLETHY	L ACETATE		
203-603-9	108-65-6	-: R10 Substance with a Community workplace exposure limit.	Flam. Liq. 3: H226	7.500%
POLY(HEXAM	ETHYLENE DIIS	SOCYANATE)		
-	28182-81-2	Xi: R36; Sens.: R43	Eye Irrit. 2: H319; Skin Sens. 1: H317	7.500%
N-BUTYL ACE	TATE			
204-658-1	123-86-4	-: R10; -: R66; -: R67 Substance with a Community workplace exposure limit.	Flam. Liq. 3: H226; STOT SE 3: H336; -: EUH066	3.000%
XYLENE				
215-535-7	1330-20-7	-: R10; Xn: R20/21; Xi: R38	Flam. Liq. 3: H226; Acute Tox. 4: H332; Acute Tox. 4: H312; Skin Irrit. 2: H315	3.000%
DIPHENYLME	THANE DIISOC	YANATE (ISOMERS AND HOMOLOG	GUES)	
-	9016-87-9	Xn: R20; Xi: R36/37/38; Xn: R40; Sens.: R42/43; Xn: R48/20	Carc. 2: H351; Acute Tox. 4: H332; STOT RE 2: H373; Eye Irrit. 2: H319; STOT SE 3: H335; Skin Irrit. 2: H315; Resp. Sens. 1: H334; Skin Sens. 1: H317	0.550%

## **Section 4: First aid measures**

## 4.1. Description of first aid measures

**Skin contact:** Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash

immediately with plenty of soap and water.

**Eye contact:** Bathe the eye with running water for 15 minutes. If irritation persists, consult a doctor

Ingestion: Call a doctor immediately.

**Inhalation:** Remove casualty from exposure ensuring one's own safety whilst doing so. If unconscious and breathing is OK, place in the recovery position. Move to fresh air in case of accidental inhalation of vapours. Consult a doctor.

#### 4.2. Most important symptoms and effects, both acute and delayed

**Skin contact:** There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

**Ingestion:** There may be soreness and redness of the mouth and throat.



PO Box 162, Needham Road, Stowmarket IP14 2ZR Tel: 01449 778 333 Fax: 01449 773 472

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest.

**Exposure may** 

cause coughing or wheezing.

**Delayed / immediate effects:** Immediate effects can be expected after short-term exposure.

**4.3.** Indication of any immediate medical attention and special treatment needed Immediate / special treatment: Eye bathing equipment should be available on the premises.

**Section 5: Fire-fighting measures** 

5.1. Extinguishing media

**Extinguishing media:** Suitable extinguishing media for the surrounding fire should be used. Carbon dioxide.

Sand. Dry chemical powder. Do not use water. Do not use water jet.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: No data available.

5.3. Advice for fire-fighters

**Advice for fire-fighters:** Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

#### **Section 6: Accidental release measures**

**6.1. Personal precautions, protective equipment and emergency procedures Personal precautions:** Refer to section 8 of SDS for personal protection details. If outside do not approach from

downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid.

6.2. Environmental precautions

**Environmental precautions:** Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

**Clean-up procedures:** Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for

disposal by an appropriate method. Ensure adequate ventilation. Do not flush with water or aqueous cleaning agents.

#### 6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS. Refer to section 13 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

**Handling requirements:** Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.

Do not handle in a confined space. Avoid the formation or spread of mists in the air. Smoking is forbidden. Wash hands before breaks and at the end of workday.



PO Box 162, Needham Road, Stowmarket IP14 2ZR

Tel: 01449 778 333 Fax: 01449 773 472

## 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in cool, well ventilated area. Keep away from sources of ignition.

Keep container

tightly closed. Prevent the build up of electrostatic charge in the immediate area. Maximum storage temperature:  $<35\,^\circ$  C. Minimum storage temperature:> 0  $^\circ$  C.

### 7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters Hazardous ingredients: ETHYL METHYL KETONE

Workplace exposure limits: Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	600 mg/m3	899 mg/m3	-	-
2-METHOXY	-1-METHYLETHYL ACETAT	E		
UK	274 mg/m3	548 mg/m3	-	-
N-BUTYL AC	ETATE			
UK	724 mg/m3	966 mg/m3	-	-
XYLENE				
UK	220 mg/m3	441 mg/m3	-	-
DIPHENYLM	ETHANE DIISOCYANATE (I	SOMERS AND HOMOLOG	GUES)	
UK	0.02 mg/m3	0.07 mg/m3	-	-

## **DNEL/PNEC Values**

**DNEL / PNEC** No data available.

#### 8.2. Exposure controls

**Engineering measures:** Ensure there is sufficient ventilation of the area.

Respiratory protection: Self-contained breathing apparatus must be available in case of

emergency. In case of

insufficient ventilation wear suitable respiratory: Filter A.

**Hand protection:** Butyl gloves. The selection of a suitable gloves does not only depend on the material,

but also upon the quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to use. The exact break trough time has to be found out by the glove manufacturer; observed.

**Eye protection:** Safety glasses. Ensure eye bath is to hand.

**Skin protection:** Protective clothing.

#### **Section 9: Physical and chemical properties**



PO Box 162, Needham Road, Stowmarket IP14 2ZR

Tel: 01449 778 333 Fax: 01449 773 472

## 9.1. Information on basic physical and chemical properties

State: Liquid Colour: Black

**Odour:** Characteristic odour

**Evaporation rate:** No data available.

**Solubility in water:** Not / slightly miscible.

Viscosity: No data available.

**Boiling point/range°C:** 79 **Melting point/range°C:** No data available.

Flammability limits %: lower: 1,8 upper: 11,5

Flash point°C: -4 Part.coeff. n-octanol/water: No data available.

**Autoflammability°C:** No autoignition **Vapour pressure:** 105 hPa **Relative density:** No data available. **PH:** No data available.

VOC g/l: 670,4 g/l - VOC-EU: 72,34% - VOC-CH: 72,34%

#### 9.2. Other information

Other information: Ignition temperature: >300°C. Density: 0,927 g/cm3 (20°C). Solvent

content: organic

solvent: 72,3%. Solids content: 27,2%.

## Section 10: Stability and reactivity

10.1. Reactivity

**Reactivity:** Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

**Hazardous reactions:** Hazardous reactions will not occur under normal transport or storage conditions.

10.4. Conditions to avoid

Conditions to avoid: No data available.

10.5. Incompatible materials

Materials to avoid: No data available.

10.6. Hazardous decomposition products
Haz. decomp. products: No data available.
Section 11: Toxicological information
11.1. Information on toxicological effects

**Hazardous ingredients:** 

### 2-METHOXY-1-METHYLETHYL ACETATE

IPR	MUS	LD50	750	mg/kg
ORL	RAT	LD50	8532	mg/kg



PO Box 162, Needham Road, Stowmarket IP14 2ZR

Tel: 01449 778 333 Fax: 01449 773 472

#### **N-BUTYL ACETATE**

ORL	MUS	LD50	6	gm/kg
ORL	RAT	LD50	10768	mg/kg

#### **XYLENE**

ORL	MUS	LD50	2119	mg/kg
ORL	RAT	LD50	4300	mg/kg
SCU	RAT	LD50	1700	mg/kg

#### DIPHENYLMETHANE DIISOCYANATE (ISOMERS AND HOMOLOGUES)

ORL	RAT	LD50	49	gm/kg
SKN	RBT	LD50	>9400	mg/kg

#### Relevant effects for mixture:

Effect	Route	Basis
Irritation	OPT	Hazardous: calculated
Sensitisation	INH DRM	Hazardous: calculated

### Symptoms / routes of exposure

**Skin contact:** There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest.

**Exposure may** 

cause coughing or wheezing.

**Delayed / immediate effects:** Immediate effects can be expected after short-term exposure.

exposure.

## **Section 12: Ecological information**

## 12.1. Toxicity

## **Ecotoxicity values:**

Specijes	Test	Value	Units
CAS 9016-87-9	-	-	-
DAPHNIA	24H EC50	>1000	mg/l
ALGAE	72H EC50	>1640	mg/l
FISH	96H LC50	>1000	mg/l

## 12.2. Persistence and degradability

Persistence and degradability: No data available.

### 12.3. Bioaccumulative potential



PO Box 162, Needham Road, Stowmarket IP14 2ZR

Tel: 01449 778 333 Fax: 01449 773 472

Bioaccumulative potential: No data available.

12.4. Mobility in soil

Mobility: No data available.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Gevaar voor water klasse 2 (D) (Zelfclassificatie): gevaar voor water.

**Section 13: Disposal considerations** 

13.1. Waste treatment methods

**Disposal operations:** Transfer to a suitable container and arrange for collection by specialised disposal

company. Must not be disposed together with household garbage or into the sewage system.

Waste code number: 08 04 09

**Disposal of packaging:** Uncleaned packagings: recommendation: Disposal according to official regulations.

**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

**Section 14: Transport information** 

14.1. UN number UN 1993

14.2. UN proper shipping name

Shipping name: FLAMMABLE LIQUID, N.O.S.

14.3. Transport hazard class(es)

Transport class: 3
14.4. Packing group
Packing group: ||

14.5. Environmental hazards

**Environmentally hazardous: No Marine pollutant: No** 

14.6. Special precautions for user

Special precautions: Warning: flammable liquids. Kemler number: 33. EMS number: F-E,S-

E.

Tunnel code: D/E Transport category: 2

**Section 15: Regulatory information** 

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

**Section 16: Other information** 

Other information

Other information: This safety data sheet is prepared in accordance with Regulation (EC)

No. 1907/2006.

## bodyline

#### **Brown Brothers Distribution Ltd**

PO Box 162, Needham Road, Stowmarket IP14 2ZR

Tel: 01449 778 333 Fax: 01449 773 472

\* indicates text in the SDS which has changed since the last revision.

**Phrases used in s.2 and s.3:** EUH066: Repeated exposure may cause skin dryness or cracking.

EUH208: Contains < name of sensitising substance>. May produce an allergic reaction.

H225: Highly flammable liquid and vapour.

H226: Flammable liquid and vapour.

H312: Harmful in contact with skin.

H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H319: Causes serious eye irritation.

H332: Harmful if inhaled.

H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335: May cause respiratory irritation.

H336: May cause drowsiness or dizziness.

H351: Suspected of causing cancer <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.

H373: May cause damage to organs <or state all organs affected, if known> through prolonged or repeated exposure <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.

R10: Flammable.

R11: Highly flammable.

R20/21: Harmful by inhalation and in contact with skin.

R20: Harmful by inhalation.

R36/37/38: Irritating to eyes, respiratory system and skin.

R36: Irritating to eyes.

R38: Irritating to skin.

R40: Limited evidence of a carcinogenic effect.

R42/43: May cause sensitisation by inhalation and skin contact.

R43: May cause sensitisation by skin contact.

R48/20: Harmful: danger of serious damage to health by prolonged exposure through inhalation.

R66: Repeated exposure may cause skin dryness or cracking.

R67: Vapours may cause drowsiness and dizziness.

### **Legend to abbreviations:** PNEC = predicted no effect level

DNEL = derived no effect level

LD50 = median lethal dose

LC50 = median lethal concentration

EC50 = median effective concentration

IC50 = median inhibitory concentration

dw = dry weight

bw = body weight

cc = closed cup

oc = open cup

MUS = mouse

# bodyline

**Brown Brothers Distribution Ltd** 

PO Box 162, Needham Road, Stowmarket IP14 2ZR

Tel: 01449 778 333 Fax: 01449 773 472

GPG = guinea pig

RBT = rabbit

HAM = hamster

HMN = human

MAM = mammal

PGN = pigeon

IVN = intravenous

SCU = subcutaneous

SKN = skin

DRM = dermal

OCC = ocular/corneal

PCP = phycico-chemical properties

**Legal disclaimer:** The above information is believed to be correct but does not purport to be all inclusive

and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.

This data sheet is compiled to be of assistance but without guarantee. Users are responsible for safe working practices. Final determination of suitability of any material is the sole responsibility of the user.